


DIN 7985 – Šrouby s půlkulatou hlavou s křížovou drážkou



DIN	7985
ISO	7045
ČSN	02 1138
drážka	Phillips
materiál	ocel třídy 4.8
povrch	ZB – zinek bílý

d.	M2,5	M3	M4	M5	M6	M8	M10
d. max.	5	6	8	10	12	16	20
k max.	2,12	2,5	3,25	3,25	4,75	6,15	7,68
m	2,7	3,1	4,6	5,3	6,8	9	10,2
bit	1	1	2	2	3	4	4

Rozměr	d, x l	Pevnost v tahu
		4.8 ZB
M2,5	2,5 x 4	•
	2,5 x 5	•
	2,5 x 6	•
	2,5 x 8	•
	2,5 x 10	•
	2,5 x 12	•
	2,5 x 16	•
M3	3,0 x 4	•
	3,0 x 5	•
	3,0 x 6	•
	3,0 x 8	•
	3,0 x 10	•
	3,0 x 12	•
	3,0 x 14	•
	3,0 x 16	•
	3,0 x 18	•
	3,0 x 20	•
	3,0 x 25	•
	3,0 x 30	•
	3,0 x 35	•
	3,0 x 40	•
3,0 x 45	•	
3,0 x 50	•	
M4	4,0 x 5	•
	4,0 x 6	•
	4,0 x 8	•
	4,0 x 10	•
	4,0 x 12	•
	4,0 x 14	•
	4,0 x 16	•
	4,0 x 18	•
	4,0 x 20	•
	4,0 x 22	•
4,0 x 25	•	
4,0 x 30	•	

Rozměr	d, x l	Pevnost v tahu
		4.8 ZB
M4	4,0 x 35	•
	4,0 x 40	•
	4,0 x 45	•
	4,0 x 50	•
	4,0 x 55	•
	4,0 x 60	•
	4,0 x 70	•
M5	5,0 x 6	•
	5,0 x 8	•
	5,0 x 10	•
	5,0 x 12	•
	5,0 x 14	•
	5,0 x 16	•
	5,0 x 18	•
	5,0 x 20	•
	5,0 x 25	•
	5,0 x 30	•
5,0 x 80	•	
M6	6,0 x 6	•
	6,0 x 8	•
	6,0 x 10	•
	6,0 x 12	•
	6,0 x 14	•
	6,0 x 16	•
	6,0 x 18	•
	6,0 x 20	•
	6,0 x 25	•
	6,0 x 30	•
6,0 x 35	•	

Rozměr	d, x l	Pevnost v tahu
		4.8 ZB
M6	6,0 x 40	•
	6,0 x 45	•
	6,0 x 50	•
	6,0 x 60	•
	6,0 x 70	•
	6,0 x 80	•
	6,0 x 90	•
	6,0 x 100	•
M8	8,0 x 12	•
	8,0 x 16	•
	8,0 x 20	•
	8,0 x 25	•
	8,0 x 30	•
	8,0 x 35	•
	8,0 x 40	•
	8,0 x 45	•
8,0 x 50	•	
8,0 x 60	•	
8,0 x 70	•	
8,0 x 80	•	

Zajistíme normy a rozměry, které nejsou uvedeny.